

"Express Mail" mailing label
Number EU474894324US
Date of Deposit September 9, 2003
I hereby Certify that this paper or fee is being deposited with the
United States Postal Service "Express Mail Post Office to
Addressee" service under 37 CFR 1.10 on the date indicated above
and is addressed to the Assistant Commissioner for Patents,
Alexandria 22313-1450.

Rosemarie Contella

Name

Rosemarie Contella

Signature

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Patent Application Of: Gan et al.

For: Discharge Methodologies For Optimizing The Performance Of
Lithium/Silver Vanadium Oxide Cells

the specification of which is being transmitted herewith

Assistant Commissioner of Patents
Alexandria, VA 22313-1450

**INFORMATION DISCLOSURE STATEMENT
Pursuant to 37 CFR 1.56**

1. Applicants submit herewith patents, publications or other information of which they are aware, which they believe may be material to the examination of this application and in respect of which there may be a duty to disclose in accordance with 37 CFR 1.56.

The filing of this Information Disclosure Statement (IDS) shall not be construed as a representation that a search has been made (37 CFR 1.56(g)), an admission that the information cited is, or is considered to be material to patentability or that no other material information exists.

The filing of this IDS shall not be construed as an admission against interest in any manner (Notice of Jan. 9, 1992, 1135 O.G. 13-25, at 25).

IDS For: Discharge Methodologies For Optimizing The Performance Of Lithium/Silver Vanadium Oxide Cells
Inventor: Gan et al.

2. Attached is Form PTO-1449. Legible copies of all items listed accompany this IDS.

3. A concise explanation of the possible relevance of the listed information items is as follows:

U.S. Patent No. 6,023,151 to Hudson et al. shows a method and device for improving the accuracy of battery/capacity, remaining capacity, and remaining run-time determinations. A specific embodiment of the subject invention relates to implementing a dynamic End of Discharge Voltage (EODV) for rechargeable batteries and battery packs. The EODV can be adjusted based on environment, operating conditions, temperature, residual capacity, cell chemistry, cell size, form factor, discharge rate and/or the number of charge/discharge cycles the battery has undergone.

U.S. Patent No. 6,307,358 to Conrad teaches a method of controlling the electrical power applied to a load comprising the steps of producing a pulse train comprising a series of pulses, defining a cycle in which a portion of the pulse train having a duration of 10% of the cycle delivers more than 20% of the total power to the load which the load receives each cycle, and supplying the pulse train to the load to supply power to the load.

U.S. Patent No. 5,739,672 to Lane shows a method for charging batteries at rates of at least five, or even ten times, normal battery capacity. By employing a pulsed charger in which various charging parameters are modified as a function of a

IDS For: Discharge Methodologies For Optimizing The Performance Of Lithium/Silver Vanadium Oxide Cells
Inventor: Gan et al.

combination of at least two 1st order sense parameters and at least one 2nd order sense parameters.

U.S. Patent No. 4,740,739 to Quammen et al. discloses a method for charging batteries where brief pulses of discharging current are superimposed upon the charging current waveform. A discharge current controller is provided in parallel with the battery having a resistor in series with an electrical switching means. The resistor dissipates the battery discharge energy as heat when the electrical switching means allows discharge current to flow. The discharge current is allowed to flow for a pulse duration selected between 50 and 100 microseconds. This brief discharge pulse is repeated at a time period on the order of 20 times the pulse duration.

U.S. Patent No. 5,367,244 to Rose et al. relates to a battery charging method comprising the steps of applying a charging current to the battery from a charge current supply, sensing the battery voltage, reducing the charging current when the battery voltage equals a target voltage and maintaining the battery voltage not greater than the target voltage during the preceding applying and reducing steps. The steps are repeated to provide a stepped current profile until the charging current is reduced to a minimum value. A similar method is described in U.S. Patent No. 5,633,576, also to Rose et al.

IDS For: Discharge Methodologies For Optimizing The Performance Of Lithium/Silver Vanadium Oxide Cells
Inventor: Gan et al.

U.S. Patent No. 5,801,515 to Chen et al. shows a method for ultrarapidly charging a battery wherein the charging current flowing into the battery is a group of pulses of multiple frequencies and multiple waveforms.

U.S. Patent No. 5,598,085 to Hassler discloses a circuit arrangement for charging rechargeable batteries that provides a continuously variable supply of electric energy to a battery to be charged.

U.S. Patent No. 6,153,949 to Soderhall discloses an electric power management system that can provide momentarily high power.

U.S. Patent No. 5,959,371 to Dooley et al. relates to a power management system for an implantable device (an implantable cardioverter/defibrillator) using a comparator to signal when the supply voltage drops below a predetermined threshold. The control electronics pause charging until the power supply voltage exceeds a predetermined threshold. In one embodiment, the amount of pause time per each charge cycle is accumulated; in another embodiment, total charge time for each charge cycle is accumulated. Another charging system for an ICD is shown in U.S. Patent No. 5,904,705 to Kroll et al.

IDS For: Discharge Methodologies For Optimizing The
Performance Of Lithium/Silver Vanadium Oxide Cells
Inventor: Gan et al.

4. The person making this statement is the agent who signs below, who makes this statement on the information supplied by the inventors and the information in the agent's file.

Respectfully submitted,

By:


Michael F. Scalise
Reg. No. 34,920

Wilson Greatbatch Technologies, Inc.
10,000 Wehrle Drive
Clarence, NY 14031
(716) 759-5810
September 9, 2003

Please type a plus sign inside this box +

PTO/SB/08A(08/00)

Approved for use through 10/31/2002, OMB 0651-0031

**INFORMATION DISCLOSURE
STATEMENT BY APPLICANT**

Sheet

1

of 6

Application Number

Filing Date

First Named Inventor

Group Art Unit

Examiner Name

Attorney Docket

August 22, 2003

Gan et al.

Attorney Docket Number 37505.0206

U.S. PATENT DOCUMENTS

FOREIGN PATENT DOCUMENTS

Examiner Signature		Date Considered	
-----------------------	--	--------------------	--

***EXAMINER:** Initial if reference considered, whether or not citation is in conformance with MPEP 609. Draw line through citation if not in conformance and not considered. Include copy of this form with next communication to applicant.

1 Unique citation designation number. 2 See attached Kinds of U.S. Patent Documents. 3 Enter Office that issued the document, by the two-letter code (WIPO Standard ST.3). 4 For Japanese patent documents, the indication of the year of the reign of the Emperor must precede the serial number of the patent document. 5 Kind of document by the appropriate symbols as indicated on the document under WIPO Standard ST.16 if possible. 6 Applicant is to place a check mark here if English language Translation is attached.